



TECHNICAL DATA SHEET

AD-Tec 35 15W-40

5 Litre & 199 Litre

Product Description

AD-TEC 35 15W-40 is a high quality mineral engine oil formulated with a balanced blend of quality base oil and additives to produce a lubricant that offers an excellent level of engine protection with outstanding cleanliness. AD-TEC 35 can be used in petrol & diesel engines both turbo and naturally aspirated.

Recommended for use by AD for the following manufacturer's specifications

ACEA: A3/B4

API: SN/CF

MB: 229.1 & 229.3

Volvo: VDS-2

VW: 502.00, 505.00 & 505.01



* Image for illustrative purposes only.

Size	Part No	Barcode
5 Litre	AZD005	5020618202431
199 Litre	AZD199	5020618202998

Product Benefits

- * Ensures lubricant performance
- * Excellent high & low temperature performance
- * Suitable for petrol and diesel engines
- * Outstanding engine cleanliness and sludge control

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Store upright and sealed in a cool, dry place out of the reach of children.

Revision: 1 | Date: 27/04/2022



TECHNICAL DATA SHEET

AD-Tec 35 15W-40

5 Litre & 199 Litre

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Base Oil	:	More Than 70%
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	12.5	<16.3	14.05
Viscosity, CCS -20°C	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		10.62
HTHS Viscosity	ASTM D4683	mPa.s	3.7		
NOACK Volatility	ASTM D5800	%		13	
Pour Point	ASTM D97	°C		-25	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			104.34
Density	ASTM D792	@ 15°C			0.889

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.