



TECHNICAL DATA SHEET

AD-Tec 35 15W-40

5 Litre & 199 Litre

Product Description

AD-TEC 35 15W-40 is a high quality mineral engine oil formulated with a balanced blend of quality base oil and additives to produce a lubricant that offers an excellent level of engine protection with outstanding cleanliness. AD-TEC 35 can be used in petrol & diesel engines both turbo and naturally aspirated.

Recommended for use by AD for the following manufacturer's specifications

ACEA: A3/B4

API: SN/CF

MB: 229.1 & 229.3

Volvo: VDS-2

VW: 502.00, 505.00 & 505.01



* Image for illustrative purposes only.

| Size | Part No | Barcode |
|-----------|---------|---------------|
| 5 Litre | AZD005 | 5020618202431 |
| 199 Litre | AZD199 | 5020618202998 |

Product Benefits

- * Ensures lubricant performance
- * Excellent high & low temperature performance
- * Suitable for petrol and diesel engines
- * Outstanding engine cleanliness and sludge control

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Store upright and sealed sealed in a cool, dry place out of the reach of children.

Revision: 1 | Date: 27/04/2022



TECHNICAL DATA SHEET

AD-Tec 35 15W-40

5 Litre & 199 Litre

Shelf Life

5 years from date of manufacture.

| | | |
|-------------------------|---|--------------------|
| Appearance | : | Amber liquid |
| Odour | : | Characteristic |
| Solubility | : | Insoluble in water |
| Percentage of Base Oil | : | More Than 70% |
| Percentage of Biodiesel | : | Nil |

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|-------|---------|
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | 12.5 | <16.3 | 14.05 |
| Viscosity, CCS -20°C | ASTM D4684 | mPa.s | | 7000 | |
| Total Base Number | ASTM D2896 | mg KOH/g | 10 | | 10.62 |
| HTHS Viscosity | ASTM D4683 | mPa.s | 3.7 | | |
| NOACK Volatility | ASTM D5800 | % | | 13 | |
| Pour Point | ASTM D97 | °C | | -25 | |
| Viscosity, Kinematic 40°C | ASTM D445 | mm ² /s | | | 104.34 |
| Density | ASTM D792 | @ 15°C | | | 0.889 |

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 27/04/2022