



TECHNICAL DATA SHEET

AD-Tec 44 5W-30

5 Litre, 20 Litre & 199 Litre

Product Description

AD-TEC 44 5W-30 is a semi synthetic engine oil designed to provide maximum protection for modern engines requiring a low viscosity oil. It is suitable for lean burn, multi-valve, injection, twin cam, turbo charged and early model Ford Zetec engines.

Recommended for use by AD for the following manufacturer's specifications

ACEA: A5/B5
API: SL/CF



* Image for illustrative purposes only.

Product Benefits

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

Size	Part No	Barcode
5 Litre	AAG005	5020618202448
20 Litre	AAG020	5020618202455
199 Litre	AAG199	5020618202462

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Store upright and sealed in a cool, dry place out of the reach of children.

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Base Oil	:	More Than 80%
Percentage of Biodiesel	:	Nil

Revision: 1 | Date: 27/04/2022



TECHNICAL DATA SHEET

AD-Tec 44 5W-30

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.7
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	8		12.3
HTHS Viscosity	ASTM D4683	mPa.s	2.9	3.5	
NOACK Volatility	ASTM D5800	%		13	
Density	ASTM D792	@ 15°C			0.85
Pour Point	ASTM D97	°C		-35	

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 27/04/2022