



TECHNICAL DATA SHEET

AD-Tec 44 5W-30

20 Litre

Product Description

AD-TEC 44 5W-30 is a semi synthetic engine oil designed to provide maximum protection for modern engines requiring a low viscosity oil. It is suitable for lean burn, multi-valve, injection, twin cam, turbo charged and early model Ford Zetec engines.

Recommended for use by AD for the following manufacturer's specifications

ACEA: A5/B5
API: SL/CF

Product Benefits

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Store upright and sealed in a cool, dry place out of the reach of children.

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Base Oil	:	More Than 80%
Percentage of Biodiesel	:	Nil



* Image for illustrative purposes only.

Size	Part No	Barcode
20 Litre	AAG020	5020618202455

Revision: 1 | Date: 27/04/2022



TECHNICAL DATA SHEET

AD-Tec 44 5W-30

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.7
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	8		12.3
HTHS Viscosity	ASTM D4683	mPa.s	2.9	3.5	
NOACK Volatility	ASTM D5800	%		13	
Density	ASTM D792	@ 15°C			0.85
Pour Point	ASTM D97	°C		-35	

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 27/04/2022