



TECHNICAL DATA SHEET

AD-Tec 30 10W/30

20 Litre

Product Description

AD-Tec 30 10W-30 is a superior mineral engine oil formulated to increase engine protection during cold start up thereby reducing engine wear. AD-Tec 30 10W-30 is a low viscosity engine oil that can help to improve fuel economy and engine cleanliness.

Recommended for use by AD for the following manufacturer's specifications

ACEA: A2/B2 & E2

API: SL/CF

Ford: WSS-M2C909-A

MB: 229.1

VW: 505.00



* Image for illustrative purposes only.

Size	Part No	Barcode
20 Litre	ABE020	5020618203018

Product Benefits

- * Ensures lubricant performance
- * Excellent high & low temperature performance
- * Suitable for petrol and diesel engines
- * Outstanding engine cleanliness and sludge control

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Keep sealed in a cool, dry place.

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber Liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water

Revision: 1 | Date: 11/03/2024



TECHNICAL DATA SHEET

AD-Tec 30 10W/30

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.9
Viscosity, CCS -25°C	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		12.12
Pour Point	ASTM D97	°c		-30	-33
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		13	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			69.24
Density	ASTM D792	@ 15°C			0.869
Viscosity Index	ASTM D2270				147.777

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 11/03/2024