



TECHNICAL DATA SHEET

AD-Tec 18 5W/30 DX 20 Litre

Product Description

AD-Tec 18 5W-30 DX is a high performance fully synthetic engine oil that provides protection against low speed pre-ignition (LSPI) issues associated with smaller capacity turbo-charged engines. AD-Tec 18 5W-30 DX is suitable for use in petrol and diesel engines with and without turbos where the manufacturer recommends this grade and specification of lubricant.

Product Benefits

- * Helps resolve LSPI issues
- * Fuel Efficient
- * Fully Synthetic

Directions for Use

Use as per manufacturer's recommendations

Storage Instructions

Store upright in a cool dry place out of the reach of children

Shelf Life

5 years from date of manufacture

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Flammability	:	Non Flammable
Percentage of Biodiesel	:	Nil



* Image for illustrative purposes only.

Size	Part No	Barcode
20 Litre	AGX020	5020618202936

Revision: 1 | Date: 11/03/2024



TECHNICAL DATA SHEET

AD-Tec 18 5W/30 DX

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.37
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.28
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
NOACK Volatility	ASTM D5800	%		13	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			61.51
Density	ASTM D792	@ 15°C			0.852

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 11/03/2024