



TECHNICAL DATA SHEET

AD ATF DIII Fluid

20 Litre & 199 Litre

Product Description

AD ATF DIII Fluid is a synthetic based multi-purpose automatic transmission fluid for automatic gearboxes. AD ATF DIII Fluid is formulated using the very latest additive technology to give a product that is frictionally stable giving optimal performance even under the most testing of conditions.

Product Benefits

- * Semi synthetic
- * Extended service life
- * Excellent protection & stability

Product Usage

AD ATF DIII fluid is designed for use in automatic transmissions manufactured by General Motors, Vauxhall and Opel to name but a few. It may also be used in other manufacturer's vehicles where recommended and as a power steering fluid where recommended.

Directions for Use

As recommended by the vehicle manufacturer.

Storage Instructions

Store sealed in a cool, dry place

Shelf Life

5 years from date of manufacture.

Appearance	:	Red liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Base Oil	:	Less than 70%
Percentage of Biodiesel	:	Nil



* Image for illustrative purposes only.

Size	Part No	Barcode
20 Litre	ACA020	5020618203032
199 Litre	ACA199	5020618203049

Revision: 1 | Date: 11/03/2024



TECHNICAL DATA SHEET

AD ATF DIII Fluid

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s			7.55
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			37.26
Density	ASTM D792	@ 15°C			0.848

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.