

# TECHNICAL DATA SHEET

### **AD ATF MV**

20 Litre & 199 Litre

#### **Product Description**

AD ATF MV is a fully synthetic automatic transmission fluid manufactured by selecting the latest quality additives and base oils to formulate a truly outstanding product. AD ATF-MV meets and exceeds a wide range of specifications and approvals making this product suitable for multi-vehicle applications.

## Recommended for use by AD for the following manufacturer's specifications

Allison: C4

ATF: SPII, SPIII & Type A, Suffix A (TASA)

Esso: LT71141ATF

Ford: Mercon®, Mercon® SP, Mercon® V, WSS-M2C166-H, WSS-M2C195-A, WSS-M2C202-B & WSS-

M2C924-C

GM: 93160393, 9986195, Dexron II D/E & Dexron III H/M

Honda: ATF-Z1 Idemitsu: K17

MB: 236.3, 236.5, 236.6, 236.7 & 236.9

Mopar: ATF+3 & ATF+4 (7176) Nissan: Matic J & Matic K Saab: 3309 & 93 165 147

Shell: LA2634 TES-295

Texaco: 7045-E, ETL-8072B & N402

Toyota: JWS3309, T-IV & WS

VW: G 052 162, G 052 990-A2 & G 055 025-A2

Voith: G607

Volvo: 11 61 540-8

ZF: TE-ML-03D, TE-ML-04D, TE-ML-14B, TE-ML-16L & TE-

ML-17C

#### **Product Benefits**

- \* Fully synthetic
- \* Outstanding wear protection
- \* Multi-vehicle applications



\* Image for illustrative purposes only.

| Size      | Part No | Barcode       |
|-----------|---------|---------------|
| 20 Litre  | AMV020  | 5020618203056 |
| 199 Litre | AMV199  | 5020618203063 |



# TECHNICAL DATA SHEET

### **AD ATF MV**

#### **Product Usage**

20 Litre & 199 Litre

AD ATF MV is designed for use in automatic transmissions where recommended also as a power steering fluid where recommended. For automatic transmissions where this specification lubricant is required.

#### **Directions for Use**

As recommended by the vehicle manufacturer.

#### **Storage Instructions**

Store sealed in a cool, dry place.

#### Shelf Life

5 years from date of manufacture.

Appearance : Red liquid

Odour : Characteristic

Solubility : Insoluble in water

Percentage of Biodiesel : Nil

| Test                       | Method    | Unit   | Min. | Max. | Typical |
|----------------------------|-----------|--------|------|------|---------|
| Viscosity, Kinematic 40°c  | ASTM D445 | mm²/s  |      |      | 38.35   |
| Density                    | ASTM D792 | @ 15°c |      |      | 0.848   |
| Viscosity, Kinematic 100°c | ASTM D445 | mm²/s  |      |      | 7.291   |

#### **Safety Precautions**

Please see our latest EC Safety Data Sheets for details.

#### **Transport Classification**

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 11/03/2024